



9³/8"

13³/4'



100 CFM/2.0 Sones @ 0.10" SP. 86 CFM @ 0.25 SP.

• Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - $11'' \times 13^{3/4''}$.

Blower Wheel

Balanced polymeric dual inlet blower wheel $5\,^{1\!/_2"}$ dia. x 4" depth, 30 paddles, secured in place using 8M hex nut.

Motor

Enclosed 4 pole electronically balanced permanently split capacitor motor (PSC); life time lubricated. Motor bearings - ball. Suitable for continuous operation. Rated 115/120 volts, 60 Hz.

• Fan Housing

23 gauge galvanized steel housing, fully sealed. Overall dimensions 10^{7} /s" x 9^{3} /s" x 7^{7} /s".

• Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

<u>Ventilating Area</u>

For bathrooms up to 100 sq. ft. For other rooms up to 125 sq. ft.

• Electrical Connections

1/2" electrical knockouts provided.

<u>Single Pack Shipping Info</u>

Box Dim: 14¹/₈" x 11⁵/₈" x 9⁵/₈" UPC: 0-8316221012-8 Shipping Weight: 11.5 lbs. Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

77/8"



107/8"

• Unit Mounting

The housing will mount in ceilings with at least 8" of clearance and through drywall thickness up to $\frac{3}{4}$ ", with a rough-in opening of 11 $\frac{1}{8}$ " x 9 $\frac{5}{8}$ ". The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

EXPANDED PERFORMANCE											
	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	104	102	100	99	98	95	83	2.0	1106	26.4	0.3

