

Reducing Bushings

Catalog Number	Description	Unit Qty.	Std. Pkg. Qty.
1161-HZ	3/4" x 1/2" Reducing Bushing	25	100
1162-HZ	1" x 1/2" Reducing Bushing	25	100
1163-HZ	1" x 3/4" Reducing Bushing	20	80
1164-HZ	1 1/4" x 1/2" Reducing Bushing	20	80
1165-HZ	1 1/4" x 3/4" Reducing Bushing	20	80
1166-HZ	1 1/4" x 1" Reducing Bushing	20	80
1167-HZ	1 1/2" x 1/2" Reducing Bushing	10	50
1168-HZ	1 1/2" x 3/4" Reducing Bushing	10	50
1169-HZ	1 1/2" x 1" Reducing Bushing	10	50
1170-HZ	1 1/2" x 1 1/4" Reducing Bushing	10	50
1171-HZ	2" x 1/2" Reducing Bushing	10	50
1172-HZ	2" x 3/4" Reducing Bushing	10	50
1173-HZ	2" x 1" Reducing Bushing	10	50
1174-HZ	2" x 1 1/4" Reducing Bushing	10	50
1175-HZ	2" x 1 1/2" Reducing Bushing	10	50

Reducing Bushings



Use to reduce the size of a taped hole or hub. NPT tapered threads.



File No. E312219

Class I, Groups C, D

Class II, Groups E, F, G

Sealing Materials

Catalog Number	Size	Unit Qty.	Std. Pkg. Qty.
CE-2571	2.2 lb	1	4

Sealing Compound with Fiber Kit



Fiber is used to separate conductors from each other and from the sealing compound. The fiber then forms a dam within the sealing fittings that allows the poured sealing compound to harden in place. The sealing compound provides a seal between and around the conductors within the fittings. UL Listed for use with Bridgeport **EYS** and **EYS-N** series sealing fittings.

Sealing Materials

Catalog Number	Size	Unit Qty.	Std. Pkg. Qty.
FB-10	3.52 Oz	1	4

Fiber



Fiber is used to separate conductors from each other and from the sealing compound. The fiber then forms a dam within the sealing fittings that allows the poured sealing compound to harden in place.