

PRODUCT DATA SHEET

Dry Moly Lube, 11 Wt Oz

No. 03084 | Item# 1003351 | Case# 1003350

Product Description Lowers friction, prevents galling and helps to reduce

torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and

dust build-up.

Applications Gaskets, transfer belts, conveyor belts, motors, plant

machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels,

gears, chains & hoists

Unit Package Description 16 Ounce Aerosol

Brand **CRC**

Generic Description 1 Dry Film Lubricant

Net Fill 11 Wt Oz

UPC Code 078254030845

Unit Dimensions 7.75H x 2.63W x 2.63D in

12 Units Per Case

Case Dimensions 8.6H x 8.4W x 11.3D in

Cases Per Pallet 133 Case Weight 12 lbs

I 2 of 5 Code 30078254030846

Dark Gray Viscous Liquid **Appearance** Molybdenum Disulfide Base Type

Flash point (F) -20°F -29°C Flash point (C)

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.71 Plastic Safe No Film Type Dry **Evaporation Rate** Fast

Working Temp (F) 650°F (Continuous) / 750°F (Intermittent) Working Temp (C) 343.3°C (Continuous) 398.9°C (Intermittent)

Last revised: 11/28/2017

Page 1 of 2



Dry Moly Lube

de Molibdeno

NGER: EXTREMELY

Non-Conductive, Dry Film

deal with High Temperature

No es Conductor, Capa Seca

^{Ideal} para las Altas Temperaturas

HARMFUL OR FATAL VED, VAPOR HARMFUL RRITATION, MAY

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair

of CRC Industries, Inc.



PRODUCT DATA SHEET



Hydrocarbon

Aerosol Flammability Level

Aerosols, Flammable, Limited Quantity

DOT Proper Shipping Name VOC % (Consumer Product

61.8

Ш

VOC g/L (Consumer Product def)

438.78

VOC lbs/gal (Consumer

3.66

Prod def)

Dry Film Lubricant

VOC Category

Removal (How To)

Remove with a heavy duty degreaser.

Dry Moly Lube

Lubricante Seco de Molibdeno

Non-Conductive, Dry Film ideal with High Temperature

lio es Conductor, Capa Seca ideal para las Altas Temperaturas

DANGER: EXTREMELY
RAMMBLE HARMFUL OR FATAL
SMALLOWED. VAPOR HARMFUL
ULSES FOR IRRITATION, MAY

Last revised: 11/28/2017

Page 2 of 2

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.

