



Powering Business Worldwide

pe.eaton.com

High Speed Fuse

FWH-020A6F

UPC:051712796729

Dimensions:

- **Height:** .25 IN
- **Length:** 1.25 IN
- **Width:** .25 IN

Weight:.4 LB

Warranties:

- Not Applicable

Specifications:

- **Type:** FWH, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Voltage Rating:** 500 Vac/dc (35-800A only)
- **Interrupt Rating:** 50 kAIC at 0.25-20A, 20 kAIC at 25-30A
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Current Rating:** 20A RMS (200% minimum opening current at rated voltage)
- **Pre Arc (I²T):** 75
- **Clearing (I²T):** Clearing at 500V: 259
- **Connection:** Ferrule end X ferrule end
- **Service Response Time:** greater than 30 Min at 150%, greater than 30 Min at 200%, greater than or equal to 10 S at 300%
- **Watt Losses:** 4.26W

Supporting documents: No Data

Certifications:

- UL Recognized
- CSA Certified

Product compliance:



- CE Marked

© 2016 Eaton. All rights reserved.