



Powering Business Worldwide

pe.eaton.com

High Speed Fuse

FWH-6.30A6F

UPC:051712796682

Dimensions:

- **Height:** .3125 IN
- **Length:** .394 IN
- **Width:** 43.307 IN

Weight:.4 LB

Warranties:

- Not Applicable

Specifications:

- **Type:** FWH, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Voltage Rating:** 1000 Vdc
- **Interrupt Rating:** 50 kAIC at less than or equal to 20% pf (.25-20A), 20 kAIC at less than or equal to 20% pf (25-30A)
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Current Rating:** 6.30 A RMS (300% minimum opening current at rated voltage)
- **Pre Arc (I²T):** 36
- **Clearing (I²T):** Clearing at 500V: 90
- **Connection:** Ferrule end X ferrule end
- **Service Response Time:** less than 30 Min at 150%, greater than 30 Min at 200%, greater than or equal to 10 S at 300%
- **Watt Losses:** 2.3W

Supporting documents: No Data

Certifications:

- UL Recognized
- CSA Certified



Product compliance:

- CE Marked

© 2016 Eaton. All rights reserved.