

Ferrule style high speed fuse links

FWP-100A22F

UPC:051712370882

Dimensions:

- Height: 50 MM
- Length: 58 MM
- Width: 23 MM

Weight: .042 KG

Warranties:

• Not Applicable

Specifications:

- Type: FWP, Ferrule style
- Application: DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- Amperage Rating: 100A
- Voltage Rating: 700 Vac (IEC), 700 Vdc (UL)
- Interrupt Rating: 200 KAIC, 50 KAIC at 300 Vdc
- Fuse Indicator: Non Indicating
- Packaging Type: Standard
- Used With: Finger safe holders/blocks and striker
- Pre Arc (I2T): 1100
- Clearing (I2T): Clearing at Rated voltage: 15,600
- Minimum Melting: 110 I2t (A2 Sec)
- Diameter: 22 MM
- Material: Ceramic
- Color: White
- Class: Class aR
- Connection: Ferrule end X ferrule end
- Watt Losses: 16.5W
- Mounting: Fuse holder and blocks

pe.eaton.com



- Quantity: 10
- Fuse Size: 22 x 58 mm

Supporting documents:

• 100AMP 700V ac 22 X 58MM FERRULE

Certifications:

- CSA Certified
- UL Recognized

Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.