# North American Standards -General Purpose

## **Gland Type:**

Non-armoured

### Cable Type:

Non-armoured and tray cable

## **Certifications and Compliances:**


• cULus Listed - UL File E23223

### **SELECTION TABLE**

Entry Thread Size 'A'		Outer Sheath 'E'	
NPT Size	NPT Catalog #	Min	Max
3/8"	NCG38 35	0.10	0.35
1/2"	NCG50 50	0.20	0.50
3/4"	NCG75 75	0.35	0.75
1"	NCG100 100	0.55	1.00

All dimensions in inches unless otherwise noted.





### **NCG Features:**

- Standard material is polyamide 6
- Weatherproof seal on outer sheath of cable
- Standard neoprene seal suitable for use in operating temperatures -25° to 40°C
- Available with NPT threads

# POLYAMIDE LOCK NUT SELECTION TABLE

Size	Catalog #		
3/8"	10N		
1/2"	11N		
3/4"	12N		
1"	13N		

## **Gland Type:**

Non-armoured

### Cable Type:

Non-armoured and tray cable


## **Certifications and Compliances:**

- cULus Listed UL File E23223
- NEMA 3, 4X

### **SELECTION TABLE**

NPT	NPT	Cable Acceptance Range 'E'		Gland Length (Less Entry)	External Diameter
Size	Catalog #	Min	Max	'F'	'G'
1/2"	NCGB1231	0.25	0.42	2.25	1.33
1/2"	NCGB1232	0.40	0.57	2.25	1.33
3/4"	NCGB2233	0.54	0.68	2.52	1.58
3/4"	NCGB2234	0.64	0.78	2.52	1.58
1"	NCGB3235	0.76	0.91	3.19	2.02
1"	NCGB3236	0.89	1.03	3.19	2.02

All dimensions in inches unless otherwise noted.



### **NCGB Features:**

- Standard material is thermoplastic polyester
- Tightens by hand to create a watertight seal
- Gasket on entry threads included
- Compact design allows close grouping of connectors
- Available with NPT threads