


# 97589 - F13DBX23/841/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse







#### **CAUTIONS & WARNINGS**


#### Caution

· Lamp may shatter and cause injury if broken

- Remove and install by grasping only plastic portion of the lamp.

### **GRAPHS & CHARTS**

Graphs\_Spectral Power Distribution



#### NOTES

• Based on 60Hz reference circuit.

• Fluorescent lamp lumens decline during life

#### **GENERAL CHARACTERISTICS**

Lamp Type

Bulb Base Equivalent Wattage Rated Life Starting Temperature (MIN) Cathode Resistance LEED-EB MR Credit

Additional Info Primary Application Compact Fluorescent - Plug-In T4 GX23-2 60.0 W 10000.0 hrs -4.0 °C 10.5 Ohm 438 picograms Hg per mean lumen hour TCLP compliant Facilities;Retail Display;Hospitality;Office;Restaurant;W

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens810.0Mean Lumens685.0Nominal Initial Lumens per Watt62Color Temperature4100.0 KColor Rendering Index (CRI)82.0

#### **ELECTRICAL CHARACTERISTICS**

Wattage13.0Open Circuit Voltage Across198.0 VStarter (MIN)198.0 VLamp Current0.285 ASupply Current Frequency60.0 Hz

#### DIMENSIONS

Maximum Overall Length (MOL)	4.8400 in(122.9 mm)
Nominal Length	4.700 in(119.4 mm)
Bulb Diameter (DIA)	0.312 in(7.9 mm)

## **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 0.312 in(7.9 mm)

97589 F13DBX23/841/ECO BUNDLE

043168975896