

# 97599 - F18DBX/830/ECO4P

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse









## **CAUTIONS & WARNINGS**

#### Caution

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

#### **GENERAL CHARACTERISTICS**

Lamp Type Compact Fluorescent - Plug-

Bulb T4 Base G24q-2 Equivalent Wattage (NOM) 65.0 W

17000.0/20000.0 h Rated Life (NOM)

Starting Temperature (MIN) 0.0 °C Cathode Resistance (NOM) 6.05 Ohm Mercury Content (NOM) 3.0 mg Picograms of Mercury (NOM) 181.9 pg

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant Facilities:Retail

198.0 V

**Primary Application** Display; Hospitality; Office; Restaurant; Wa

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1250.0 Mean Lumens (NOM) 970.0 Nominal Initial Lumens per Watt 69.44444

(NOM)

Color Temperature (NOM) 3000.0 K Color Rendering Index (CRI) 82.0

(NOM)

### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 18.0 Voltage (NOM) 100.0 Current (max) (NOM) 5.25 A Open Circuit Voltage (after 220.0 V preheating) (MAX)

Open Circuit Voltage Across

Starter (MIN)

Lamp Current (NOM) 0.22 A Preheat Voltage (MIN) 4.25 V Current Crest Factor (MAX) 1.7 Supply Current Frequency 60.0 Hz

(NOM)

## **DIMENSIONS**

5.800 in(147.3 mm) Maximum Overall Length (MOL) (NOM) Nominal Length (NOM) 5.800 in(147.3 mm) Base Face to Top of Lamp 5.200 in(132.1 mm) (NOM)

#### **PRODUCT INFORMATION**

**Product Code** 97599

Description F18DBX/830/ECO4P ANSI Code 60501-IEC-2518-2 **BUNDLE** 

50

Standard Package

Standard Package GTIN Standard Package Quantity

Sales Unit Unit No Of Items Per Sales Unit 1 No Of Items Per Standard 50

Package

UPC 043168975995

#### NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Cold cathode resistance is approximately 6.0 Ohms.
- Fluorescent lamp lumens decline during life