

# 97633 - F42TBX/827/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse









# **CAUTIONS & WARNINGS**

#### Caution

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

### **GENERAL CHARACTERISTICS**

Compact Fluorescent - Plug-Lamp Type Bulb T4 Base GX24-q4 Equivalent Wattage (NOM) 190.0 W 17000.0 h Rated Life (NOM) Starting Temperature (MIN) -18.0 °C Cathode Resistance (NOM) 2.7 Ohm Mercury Content (NOM) 3.0 mg 65.6 pg Picograms of Mercury (NOM)

Rated Life (rapid start) @ Time 17000.0 @ 3.0/20000.0 @

12.0 h

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant

Facilities;Retail **Primary Application** 

Display; Hospitality; Office; Restaurant; W

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 3200.0 Mean Lumens (NOM) 2690.0 Nominal Initial Lumens per Watt 76.19048 (NOM) Color Temperature (NOM) 2700.0 K

Color Rendering Index (CRI) 82.0

(NOM)

# **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 42.0 Voltage (NOM) 120.0 Current (max) (NOM) 5.25 A Open Circuit Voltage (after 265.0 V preheating) (MAX) Open Circuit Voltage (MIN) 515.0 V Lamp Current (NOM) 0.32 A Preheat Voltage (MIN) 4.25 V Current Crest Factor (MAX) 1.7 Supply Current Frequency 20.0 Hz

# **DIMENSIONS**

Maximum Overall Length 6.400 in(162.6 mm) (MOL) (NOM) Nominal Length (NOM) 6.400 in(162.6 mm) Base Face to Top of Lamp 5.770 in(146.6 mm)

(NOM)

(NOM)

# PRODUCT INFORMATION

**Product Code** 97633 F42TBX/827/A/ECO Description ANSI Code 60901-IEC-7442-2

Standard Package Case

10043168976333 Standard Package GTIN

Standard Package Quantity 10 Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 10

Package

UPC 043168976336

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life