

Plenum

Features

- E-Z Strip Buffer For Contractor-Friendly Termination
- Durable Aluminum Interlock Armor
- Premium Bend-Insensitive Fiber For Enhanced Optical Performance

Ordering Information

| Description | Fiber Type | Catalog No. | UPC No. |
|--|---------------|--------------------|--------------|
| Indoor Interlock Armored Tight Buffer, 6 Fiber, Plenum, Aqua | OM3 Multimode | HFCD15006P3 | 662620332086 |

Listings

ANSI/ICEA S-83-596
TIA-568.3-D
NFPA-262/UL910/CSA FT-6
Telcordia GR-409 and GR-20

Specifications

| | |
|------------------------|-------------------------------------|
| Fiber Coating | 900 Micron PVC Tight Buffer |
| Cable Diameter in (mm) | 0.63 (16) |
| Cable Weight (lb/kft) | 165 |
| Construction | Single Unit, Aramid Strength Member |
| Armor | Aluminum Interlock |

Performance

Cable Attenuation (dB/km at 850/1300 nm)

3.5/1.5

Maximum Installation Pulling Load (lb)

150

Maximum Operating Temperature

-4°F to +158°F (-20°C to +70°C)

Minimum Bend Radius, In-Service in (cm)

2.1 (5.3)



Accessories

| | |
|---------------------------|--------------------|
| Fiber Strip Tool | OFSTRIP2 |
| Splice Tray, 12 Fusion | STRAY12F |
| Splice Tray, 24 Fusion | STRAY24F |
| Splice Protection Sleeves | FSHST401025 |

Online Resources

[eCatalog](#)