

## Plenum

### Features

- E-Z Strip Buffer For Contractor-Friendly Termination
- Durable Aluminum Interlock Armor
- Premium Bend-Insensitive Fiber For Enhanced Optical Performance

### Ordering Information

Description	Fiber Type	Catalog No.	UPC No.
Indoor Interlock Armored Tight Buffer, 24 Fiber, Plenum, Aqua	OM3 Multimode	<b>HFCD15024P3</b>	662620332130

### Listings

ANSI/ICEA S-83-596  
TIA-568.3-D  
NFPA-262/UL910/CSA FT-6  
Telcordia GR-409 and GR-20

### Specifications

Fiber Coating	900 Micron PVC Tight Buffer
Cable Diameter in (mm)	0.69 (17.4)
Cable Weight (lb/kft)	188
Construction	Single Unit, Aramid Strength Member
Armor	Aluminum Interlock

### Performance

#### Cable Attenuation (dB/km at 850/1300 nm)

3.5/1.5

#### Maximum Installation Pulling Load (lb)

300

#### Maximum Operating Temperature

-4°F to +158°F (-20°C to +70°C)

#### Minimum Bend Radius, In-Service in (cm)

3.2 (8.1)



### Accessories

Fiber Strip Tool	<b>OFSTRIP2</b>
Splice Tray, 12 Fusion	<b>STRAY12F</b>
Splice Tray, 24 Fusion	<b>STRAY24F</b>
Splice Protection Sleeves	<b>FSHST401025</b>

### Online Resources

[eCatalog](#)