



Twist-Lock® Devices

Accessories

for 15 Ampere 2 and 3 Wire Duplex, Single Receptacles and Flanged Devices



SS8

SS7



HBL5206WO



HBL5221



HBL7423WO



WP1

Wallplates, 1-Gang

Description	Color	Duplex Receptacles	Single Receptacles with Face Dia. 1.40" (35.6)
Nylon, smooth.	Brown Ivory	NP8 NP8I	NP7 NP7I
Stainless steel 302/304, .035 in. (0.9), horizontal brushed finish.		SS8	SS7
Stainless steel 430, .035 in. (0.9), horizontal brushed finish.		SS8L	SS7L
Brass .04 in. (1.0), horizontal brushed finish.		SB8	SB7
Aluminum .05 in. (1.3), horizontal brushed finish.		SA8	SA7

IP44

SUITABILITY

Weatherproof Covers

Description	Duplex Receptacles	Single Receptacles with Face Dia. 1.40" (35.6)
Cast aluminum, for standard horizontal box mount.	HBL5205WO	—
Same as above except FS/FD box mount.	HBL5206WO	—
Cast aluminum vertical FS/FD box mount.	—	HBL7420
Gray thermoplastic, vertical standard box mount, corrosion resistant.	HBL5222*	—
Same as above except yellow.	HBL52CM22*	—
Gray thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL5221*	HBL7423WO
Yellow thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21*	HBL74CM23WO
White thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21W*	—

IP44

SUITABILITY

Weatherproof Covers for 15A Flanged Inlets and Receptacles

Description	Catalog Number
Gray thermoplastic, corrosion resistant.	WP1

Note: All weatherproof plates listed above are UL Listed for wet and damp locations with cover closed.

Those with suffix WO are UL Listed with cover open.

See Section K, page K-24 for more information.

* IP20 Suitability only.