



A.

## IG1200RC3 Plastic Housing

- Type 1 or 2 SPD applications
- Green LED indicator provides status of protection
- Type 3R rainproof enclosure
- 5.65" H x 4.18" W x 3.33" D
- 3 modes of surge protection (L1-N, L2-N, L1-L2)
- 3-year product warranty
- \$7,500 connected equipment warranty for 3 years on appliances and electronics



B.

## IG1240RC3 Plastic Housing

- Type 1 or 2 SPD applications
- Green LED indicator provides status of protection
- Type 3R rainproof enclosure
- 5.65" H x 4.18" W x 3.33" D
- 6 modes of surge protection: L1-N, L2-N, L1-G, L2-G, N-G, L1-L2
- 5-year product warranty
- \$10,000 connected equipment warranty for 5 years on appliances and electronics



C.

## IG3240RC3 Metal Housing

- Type 1 or 2 SPD applications
- Green LED indicator provides status of protection
- Type 3R rainproof enclosure
- 5.28" H x 4.4" W x 3.25" D
- 6 modes of surge protection: L1-N, L2-N, L1-G, L2-G, N-G, L1-L2
- 10-year product warranty
- \$25,000 connected equipment warranty for 10 years on appliances and electronics

Model #	Service Voltage	No. of Leads	Lead Length	Wiring Config.	Nominal Discharge Current	MCOV*	SCCR**	Voltage Protection Rating (VPR)				
								L-N/G	L-N	L-G	N-G	L-L
A. <b>IG1200RC3</b>	120, 240 VAC	3	30"	L1, L2, N/G	20 kA		50 kA	700				1200
B. <b>IG1240RC3</b>	120, 240 VAC	4	30"	L1, L2, N, G	20 kA	150 L-N, N-G† 300 L-L, L-G†	50 kA	700	1200	700	1200	
C. <b>IG3240RC3</b>	120, 240 VAC	4	30"	L1, L2, N, G	20 kA		50 kA	700	1200	700	1200	

\* MCOV Maximum Continuous Operating Voltage

\*\*SCCR Short Circuit Current Rating

†Applies to all models