

## FEATURES & SPECIFICATIONS

### INTENDED USE

For use with housings L3 and L3R.

### CONSTRUCTION

Antique bronze, oil-rubbed bronze, brushed nickel, white and black finishes are one piece aluminum open reflectors with integral flange.

### INSTALLATION

Socket to trim interface.

Retaining clips pull and snap onto top of reflector to hold trim inside housing.

### LISTINGS

U.L. Listed to U.S. and Canadian safety standards.

Damp location listed.

Pull on clip Patent # (U.S.) 5707143, (Canada) 2193902.

### WARRANTY

1-year limited warranty. Complete warranty terms located at

[www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.


Catalog Number
Notes
Type

3" Finishing Trim

# 3B1

BAFFLE SHALLOW

Narrow Flange




### Specifications

Height: 4-3/4" (12.1)

Lamp opening: 3-1/2" (8.9)

Diameter: 4-7/8" (12.4)

All dimensions are inches (centimeters) unless otherwise indicated.



### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

**Example: 3B1**

3B1	
Series	Finish
<b>3B1</b>	<b>(blank)</b> Black baffle, white flange
	TRMW Black baffle, matte white flange
	<b>W</b> White baffle
	MW Matte white baffle
	BN Brushed nickel baffle
	ORB Oil-rubbed bronze baffle

Housing Compatibility: <i>Housing and trim ordered separately.</i>			
Application	Source	Maximum wattage	Housing
IC	Incandescent	35 PAR20	L3, L3R
		50 PAR20 <sup>1</sup>	
		50 R20 <sup>1</sup>	
Non-IC	Incandescent	50 PAR20	L3, L3R

### Notes

1 White baffle (3B1W) only.

