

Catalog Number: Item Description: UPC Code:

U5891-X-2/200-MLK-BL 320A 4T RL OU HD LVR 12CT 784572607842

Brand Name:	Milbank		
Туре:	Ringless N	1eter Socket	
Application:	Meter Soc Center	ket With Main And Load	
Standard:	UL Listed		
Voltage Rating:	Up to 240	Volts Alternating Current	
Amperage Rating:	320 Continuous Ampere		
Phase:	1 Phase		
Frequency Rating:	60 Hertz		
Number Of Cutouts:	2		
Cutout Size:	200 Ampere Main Breaker		
Cable Entry:	Overhead and Underground, Side Wireway		
Terminal:	3/8 Inch Stud Line Side and Single Mechanical Load Side		
Mounting:	Surface Mount		
Enclosure:	Type 3R, G90 Galvanized Steel with Powder Coat Finish		
Additional Specifications:		Number of Jaws:4 Terminal	
		Hub Opening and Closing Plates:Large Closing Plate	
		Hub Opening and Closing Plates:Large Closing Plate	
		Hub Opening and Closing Plate	s:Large Closing Plate
		Hub Opening and Closing Plate	s:Large Closing Plate



Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

Hub Opening and Closing Plates:Large Closing Plate