

MINITERMS

**Female Disconnects:
Piggyback, Sleeved Barrel
& Fully Insulated**
P, IFS, IF SERIES

FEATURES

**VINYL/
UN-INSULATED/
NYLON:**

Electro tin plated copper,
600V, 105 °C, Vinyl



NYLON:

Electro tin plated copper,
600V, 105 °C, Nylon, Female
fully insulated quick disconnect
with seamed barrel.



NYLON:

Female, fully insulated quick
disconnect with brazed seam
600V, 105 °C, Nylon



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Female Piggyback	Vinyl	22-18	0.250	
Female Piggyback	Vinyl	16-14	0.250	
Female Piggyback	Vinyl	12-10	0.250	UL
Female Piggyback	Un-insulated	16-14	0.250	
Female Piggyback	Nylon	22-18	0.250	
Female Piggyback	Nylon	16-14	0.250	
Female Fully Insulated Sleeved Barrel	Nylon	22-18	0.110	
Female Fully Insulated Sleeved Barrel	Nylon	22-18	0.110	
Female Fully Insulated Sleeved Barrel	Nylon	22-18	0.250	
Female Fully Insulated Sleeved Barrel	Nylon	16-14	0.250	
Female Fully Insulated Sleeved Barrel	Nylon	12-10	0.250	
Female Fully Insulated	Nylon	22-18	0.110	UL
Female Fully Insulated	Nylon	22-18	0.110	UL
Female Fully Insulated	Nylon	22-18	0.187	UL
Female Fully Insulated	Nylon	22-18	0.187	UL
Female Fully Insulated	Nylon	22-18	0.250	
Female Fully Insulated	Nylon	16-14	0.187	
Female Fully Insulated	Nylon	16-14	0.187	UL
Female Fully Insulated	Nylon	16-14	0.250	
Female Fully Insulated	Nylon	16-14	0.250	NON-UL
Female Fully Insulated	Nylon	12-10	0.250	





		"S" PACKS		PRO PACKS		STD PACKS		BULK PACKS	
L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.826	0.259	-	-	-	-	P22-250-3V	100	P22-250-3V-BULK	1000
0.826	0.259	P16-250-3V-S	15	P16-250-3V-P	40	P16-250-3V	100	P16-250-3V-BULK	1000
1.010	0.250	-	-	-	-	P12-250-3V	50	P12-250-3V-BULK	500
0.677	0.295	-	---	-	---	P16-250-3	100	P16-250-3-BULK	1000
0.866	0.259	-	-	-	---	P22-250-3N	100	P22-250-3N-BULK	1000
0.866	0.259	-	-	-	-	P16-250-3N	100	P16-250-3N-BULK	1000
0.800	0.230	-	-	-	-	IFS22-110-2N	100	IFS22-110-2N-BULK	1000
0.800	0.230	-	-	-	-	IFS22-110-3N	100	IFS22-110-3N-BULK	1000
0.890	0.380	-	-	-	-	IFS22-250-3N	100	IFS22-250-3N-BULK	1000
0.890	0.380	-	-	-	-	IFS16-250-3N	100	IFS16-250-3N-BULK	1000
1.040	0.380	-	-	-	-	IFS12-250-3N	50	IFS12-250-3N-BULK	500
0.800	0.230	-	-	-	-	IF22-110-2N	100	IF22-110-2N-BULK	1000
0.800	0.230	-	-	-	-	IF22-110-3N	100	IF22-110-3N-BULK	1000
0.780	0.320	-	-	-	-	IF22-187-2N	100	IF22-187-2N-BULK	1000
0.780	0.320	-	-	-	-	IF22-187-3N	100	IF22-187-3N-BULK	1000
0.866	0.259	-	-	-	-	IF22-250-3N	100	IF22-250-3N-BULK	1000
0.780	0.320	-	-	-	-	IF16-187-2N	100	IF16-187-2N-BULK	1000
0.780	0.320	-	-	-	-	IF16-187-3N	100	IF16-187-3N-BULK	1000
0.866	0.259	IF16-250-3N-S	12	IF16-250-3N-P	50	IF16-250-3N	100	IF16-250-3N-BULK	1000
0.955	0.395	IF16-250-3N-IG-S	10	-	-	IF16-250-3N-IG	100	IF16-250-3N-IG-BULK	1000
0.964	0.259	IF12-250-3N-S	12	IF12-250-3N-P	30	IF12-250-3N	50	IF12-250-3N-BULK	500