

**Male Disconnects:
Fully Insulated & Male/
Female Adapter**

M, IM, FCT SERIES

FEATURES

VINYL:

Electro tin plated, vinyl (PVC) 300V, 75 °C. Brazed seam, Male disconnect

UN-INSULATED:

Electro tin plated copper, 600V, 105 °C. Brazed seam, Male disconnect

NYLON:

Fully insulated male disconnect. Brazed seam, nylon, 300V, 105 °C.

UN-INSULATED-BARE:

Turned up edges give this quick disconnect adaptor more safety and reliability. 600V, 105 °C.



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Male Fully Insulated Barrel	Vinyl	22-18	0.250	
Male Fully Insulated Barrel	Vinyl	16-14	0.187	
Male Fully Insulated Barrel	Vinyl	16-14	0.250	
Male Fully Insulated Barrel	Vinyl	12-10	0.250	
Un-Insulated Male Barrel	Un-insulated	16-14	0.187	NON-UL
Un-Insulated Male Barrel	Un-insulated	16-14	0.250	NON-UL
Un-Insulated Male Barrel	Un-insulated	12-10	0.250	NON-UL
Male Fully Insulated	Nylon	22-18	0.250	
Male Fully Insulated	Nylon	22-18	0.250	UL
Male Fully Insulated	Nylon	16-14	0.187	
Male Fully Insulated	Nylon	16-14	0.250	
Male Fully Insulated	Nylon	16-14	0.250	
Male Fully Insulated	Nylon	12-10	0.250	
Male Fully Insulated	Nylon	12-10	0.250	UL
Male/Female Adapter	Un-insulated	12-10	0.250	



		"S" PACKS		PRO PACKS		STD PACKS		BULK PACKS	
L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.834	0.249	M22-250-3V-S	25	–	–	M22-250-3V	100	M22-250-3V-BULK	1000
0.755	0.188	–	–	–	–	M16-187-2V	100	M16-187-2V-BULK	1000
0.834	0.249	M16-250-3V-S	30	M16-250-3V-P	100	M16-250-3V	100	M16-250-3V-BULK	1000
0.933	0.249	M12-250-3V-S	25	M12-250-3V-P	50	M12-250-3V	50	M12-250-3V-BULK	500
0.630	0.240	–	–	–	–	M16-187-2	100	M16-187-2-BULK	1000
0.630	0.240	–	–	–	–	M16-250-3	100	M16-250-3-BULK	1000
0.765	0.250	–	–	–	–	M12-250-3	50	M12-250-3-BULK	1000
0.925	0.249	–	–	–	–	IM22-250-3N	100	IM22-250-3N-BULK	1000
0.904	0.249	–	–	–	–	M22-250-3N	100	M22-250-3N-BULK	1000
0.795	0.188	–	–	–	–	M16-187-2N	100	M16-187-2N-BULK	1000
0.925	0.249	IM16-250-3N-S	20	IM16-250-3N-P	30	IM16-250-3N	50	IM16-250-3N-BULK	1000
0.874	0.249	–	–	–	–	M16-250-3N	100	M16-250-3N-BULK	1000
1.062	0.249	–	–	–	–	IM12-250-3N	50	IM12-250-3N-BULK	500
1.061	0.249	–	–	–	–	M12-250-3N	50	M12-250-3N-BULK	500
0.529	0.549	FCT12-250-3-S	10	–	–	FCT12-250-3	50	FCT12-250-3-BULK	1000