

# CABLE TIES Velcro Ties V SERIES



## FEATURES

- Unique back-to-back fastening system: a self-gripping, double-sided strap that is easy to use and cost effective.
- Molded high performance polyethylene hook fastener laminated on to a non-woven polyester loop.
- Low peel strength allows for easy entry or removal by the user yet the average shear strength is 3.0 PSI, which increases substantially with each circular rotation. Will not over-cinch delicate cable and fiber optics.
- For use with cord and cable management, wire harnesses, inventory control, fibre optics, packaging, in-plant maintenance, etc.
- Allow for a minimum 2" overlap when installing.
- Available in five colors.

## RATINGS



MAX. WIRE/ CABLE SIZE	CAT. NO.	COLOR	MAX. BUNDLE DIAMETER	LENGTH (IN.)	WIDTH (IN.)	PCS. PER. PKG.	PKG. PER. CTN.
8"	<b>V850</b>	Black	1.750	8"	0.500	10	25
	<b>V850-2</b>	Red	1.750	8"	0.500	10	25
	<b>V850-3</b>	Orange	1.750	8"	0.500	10	25
	<b>V850-4</b>	Yellow	1.750	8"	0.500	10	25
	<b>V850-6</b>	Blue	1.750	8"	0.500	10	25
12"	<b>V1250</b>	Black	3.000	12"	0.500	10	20
	<b>V1250-2</b>	Red	3.000	12"	0.500	10	20
	<b>V1250-4</b>	Yellow	3.000	12"	0.500	10	20
	<b>V1250-6</b>	Blue	3.000	12"	0.500	10	20
80"	<b>V875</b>	Black	Perforated Every 8"	80"	0.75	1	10
10'	<b>V1275</b>	Black	Perforated Every 12"	10'	0.75	1	10
15'	<b>V180</b>	Black	-	15'	0.75	1	10
75'	<b>V900</b>	Black	-	75'	0.75	1	3
600'	<b>V7200</b>	Black	-	600'	0.75	1	1

\*Note: Rolls of Velcro tape can be cut to desired length.