

## WP13LEDPC

Small Wallpack LED With Photocontrol

12.6 Watt fixture  
615 lumens output  
4700K color  
120VAC input



PROJECT INFORMATION: \_\_\_\_\_

\_\_\_\_\_

JOB: \_\_\_\_\_

APPROVALS: \_\_\_\_\_

\_\_\_\_\_

### APPLICATIONS

- Commercial building
- Shopping centers
- Schools
- Apartment complex entry or perimeter security lighting applications

### CONSTRUCTION

- Die cast rear housing
- Polycarbonate front housing
- Architectural bronze UV resistant powder coat finish

### LIFESPAN

- L70 Calculated: 108,000
- L70 Reported: >60,000

### OPERATING TEMPERATURE

- Minimum: -40 °C
- Maximum: 50 °C

### DRIVER INFORMATION

- Type: Constant current
- Class 2: UL8750
- RoHS Compliant: Yes
- IP Rating: IP65
- Efficiency: 80%
- PFC: >0.9
- EMI: EN55015, EN61347
- FCC: Class B

### ELECTRICAL

- AC Input Range: 120VAC
- Input Current: 0.12A @ 120VAC
- Input Power: 12.6W
- Input Frequency: 47~63Hz
- Power Factor: >0.9
- THD: <0.2
- Surge Protection: 4kV
- Dimmable Option: Yes

### LEDs

- 3 Hi Power LEDs: 615 lumens
- LED Drive Current: 1000mA
- Lumens per Watt: 49
- Watts: 4.2W
- Color Temperature: 4700K
- Color Index: 70+



### AGENCY LISTINGS

- UL Listed: Yes
- cUL Listed: Yes
- RoHS Compliant: Yes
- Wet Locations: Suitable

### WARRANTY

5-year Limited.  
See website for details.  
[www.nsiindustries.com](http://www.nsiindustries.com)

### DIMENSIONS



### ORDERING INFO

CAT. NO.	SYSTEM WATTS	LUMEN OUTPUT	COLOR	MA	INPUT VOLTAGE	CRI	STARTING TEMP.	EQUIVALENT
WP13LEDPC	12.6	615	4700K	1000	120VAC	70+	-40 °C	50W - 70W MH

### PHOTOMETRIC REPORTS

