



# High Output T12

## F72T12/D/HO ALTO 15PK

Philips T12 fluorescent lamps provide high performance in a wide range of sizes, shapes, and types.

### Product data

General Information		Operating and Electrical	
Cap-Base	R17D [ R17d (RDC)]	Power (Rated) (Nom)	85 W
Life 3-Hr Start [Hrs]	12000 h	Mechanical and Housing	
Features	ALTO® (ALTO)	Cap-Base Information	Green Base
Footnotes Fluorescent/CFL 1	Approximate initial lumens are for 800 ma. operation. For 1000 ma. operation, lumens are approximately 10% higher and watts approximately 15% higher. (207)	Nominal Length (Inch)	72
Footnotes Fluorescent/CFL 2	Econ-o-watt® lamps are only recommended for use on high power factor lead, indoor ballasts that meet ANSI standards. The lamps are not recommended for use in drafty areas, or locations where the ambient temperature is less than 60°F, except as noted. Also they should not be operated on low power factor ballasts, reduced light or reduced current ballasts, dimming ballasts or emergency system inverter ballasts. (214)	Approval and Application	
		Energy Saving Product	Not Applicable
		Mercury (Hg) Content (Nom)	6.8 mg
		Product Data	
		Order product name	F72T12/D/HO ALTO 15PK
		EAN/UPC - Product	046677366537
		Order code	366534
		Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	15
		Material Nr. (12NC)	927893205402
		Net Weight (Piece)	0.001 kg
Light Technical			
Color Code	54		
Initial lumen (Nom)	5600 lm		
Color Designation	Daylight		
Design Mean Lumens	4850 lm		
Correlated Color Temperature (Nom)	6500 K		
Color Rendering Index (Nom)	79		

## High Output T12


### Warnings and Safety

- Lamp contains mercury. Manage in Accord with Disposal Laws. See: [www.lamprecycle.org](http://www.lamprecycle.org) or 1-800-555-0050

### Dimensional drawing

#### Product

F72T12/D/HO ALTO 15PK



T12 Revised Double Contact

F72T12 85W/54 HO ALTO

