

Project:		
Fixture Type:		
Location:		
Contact:		

MINGLE LED

Ceiling mount · Damp location listed

PROGRES	SLE	D)



Specifications:

Description:

One-light semi-flush LED fixture features a concentric circular pattern in a Brushed Nickel metal shade that surrounds etched parchment glass. 3000K, 90+ CRI 1,211 Lumens 71.2 lumen/watt.

Construction:

Brushed Nickel (-09) (plated)

Steel construction

Etched Parchment glass shade

LED Module is replaceable (part # 93053641)

Flicker-free dimming to 10% brightness with most ELV type dimmers $\,$

(See Dimming Notes)

Title 24 compliant

Canopy covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

Six inches of wire supplied

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

P2320-0930K9

Images:



Dimensions:

Diameter: 14" Height: 10-1/2"

Catalog number:

 Base
 Finish
 Color Temp
 CRI

 P2320
 09 - Brushed Nickel
 30K - 3000K
 9 - 90 CRI