

Project:		
Fixture Type:		
Location:		
Contact:		

TRUSS

Wall mount · Dry location listed



Specifications:

Description:

The P2839 features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

Construction:

Brushed Nickel (-09) (plated)

Steel construction

LED Module is replaceable (part #)

Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Title 24 compliant

Complies with "Americans with Disabilities Act" - ADA

Back plate covers a standard 4" hexagonal recessed outlet box

Mounting bracket for outlet box included

Six inches of wire supplied

Performance:

Number of Modules	1
Input Power	35W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1222/55.8 (LM-79) per module
ССТ	3000K
CRI	93
Life	42000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	ETL Dry location listed


P2839-0930K9

Images:



Dimensions:

Width: 22-1/2" Height: 4-3/4" Depth: 3-7/8" H/CTR: 2-3/8"



Catalog number:

Base		Finish	Color Temp	CRI
P2839	-	09 - Brushed Nickel	30K - 3000K	9 - 93 CRI



TRUSS

Wall mount · Dry location listed



P2839-0930K9

Dimming Notes:

P2839 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.