

# BROOKSIDE

Wall mount • Wet location listed



## Specifications:

### Description:

Get inspired with vintage undertones reminiscent of early 20th century train depots. This indoor/outdoor LED Wall lantern is cast aluminum. 3000K, 90+ CRI, 1,211 lumens.

### Construction:

- Gilded Iron (-71) (painted)
- Steel construction metal
- LED Module is replaceable (part # 93053641)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Title 24 compliant
- Back plate covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- Six inches of wire supplied

### Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1,112/71.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

## P5723-7130K9

### Images:



### Dimensions:

Width: 12"  
Height: 12-1/4"  
Depth: 13-1/4"  
H/CTR: 6-7/8"

### Catalog number:

Base	Finish	Color Temp	CRI
P5723	71 - Gilded Iron	30K - 3000K	9 - 90 CRI

## P5723-7130K9

### Dimming Notes:

---

P5723 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

#### Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.