

LED ceiling light with precision optics deliver smooth and uniform distribution. Ideal for retail settings, workspace lighting and other applications requiring a high output commercial grade downlight.

Color: Bronze Weight: 18.0 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info		LED Info	
Type:	Constant Current	Watts:	52W
120V:	0.53A	Color Temp:	4000K (Neutral)
208V:	0.35A	Color Accuracy:	73 CRI
240V:	0.30A	L70 Lifespan:	100,000
277V:	0.26A	Lumens:	4553
Input Watts:	60W	Efficacy:	76 LPW
Efficiency:	87%		

# **Technical Specifications**

## Listings

### **UL Listing:**

Suitable for Wet Locations. Covered Ceiling Mount Only.

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

### **LED Characteristics**

## Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### LEDs:

4x13W high-output, long-life LEDs

## **Color Consistency:**

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

# Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period

### **Color Uniformity:**

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

### **Electrical**

## Drivers:

2x26W Driver, Constant Current, Class 2, 100V-277V, 50/60 Hz, 6kv Surge Protection, 720mA, 100-277VAC 0.4 Amps., Power Factor 99%.

### THD:

13.6% at 120V

### Construction

# **Maximum Ambient Temperature:**

Suitable for use in 40°C (104°F) ambient temperatures

### **Cold Weather Starting:**

Minimum starting temperature is -40°C (-40°F)

### Housing:

Precision die-cast aluminum housing and lens frame

### Lens:

Clear tempered glass lens

#### Gaskets:

High-temperature silicone

#### Finish:

Formulated for high-durability and long lasting color

### **Green Technology:**

Mercury and UV-free. RoHS compliant components.

#### Other

## Patents:

The design of CLED52 is protected by patents pending in US, Canada, China, Taiwan and Mexico

## **Buy American Act Compliance:**


RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

# Optical

# **BUG Rating:**

B2 U1 G1

CLED52N



# **Features**

- High output ceiling light
- Precision optics deliver uniform light distribution
- 100,000-hour LED lifespan
- 5-Year, No-Compromise Warranty