LFP38B

Premium PAR38 Flood with large, molded high temperature black silicone gasket that totally seals lamp. Die cast aluminum housing. EZ Locknut. Suitable for mounting within 4' of the ground. PAR38 or PAR20, 150 watt max. Lamp not supplied.

Lamp Info		Ballast Info	
Type:	PAR20	Type:	N/A
Watts:	150W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	2,500	Input Watts:	OW
Lamp Lumens:	550	Efficiency:	N/A
Efficacy:	N/A		

Technical Specifications

UL Listing:

Suitable for wet locations.

Sockets:

Porcelain with all copper current carrying components and spring loaded center contact.

Swivels:

Fully adjustable with sure-grip locknuts. 1/2" NPS threaded arm with locking swivel fits all standard mounting covers.

Housings:

Precision die cast aluminum. Tuffy flood is molded plastic.

Lamp:

PAR38 or PAR20, 150 watt max. lamp not supplied.


Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color: Black







G H T I N G
Tech Help Line: 888 RAB-1000