




RIGID THREADED HUBS - DIE CAST ZINC

Conduit Hub, Insulated Throat Die Cast Zinc

B33



Catalog #: 1703

APPLICATIONS

For use with threaded rigid/IMC conduit to connect and bond conduit to a threadless opening in a box or enclosure
May be used in wet or dry locations

PRODUCT FEATURES

Rugged metallic construction insures mechanical protection
Insulated throat protects wires and reduces wire pulling effort
O-ring seals the assembly and provides a raintight seal
N/A

UL LISTED

Standard 514B, UL Listed E195969

CSA

C22.2 No. 18

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 3/4 in.

DRAWING DIMENSIONS

Dimension A: 1.510 in.
Dimension B: 1.685 in.
Dimension C: 3/4 in. - 14 NPT

PACKAGING

Package Type: Carton
Ship Carton Qty.: 25
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 28.10
Ship Carton Length (in.): 7.80
Ship Carton Width (in.): 5.50
Ship Carton Height (in.): 5.70
Ctn Weight (Lbs.): 7.03
UPC Number: 050169017036
I2of5: 50050169017031