




LIQUIDTIGHT SERVICE ENTRANCE CABLE CONNECTORS

Service Entrance Cable Connectors, Liquidtight - Die Cast Zinc
N/A

B80



Catalog #: 2475

APPLICATIONS

For use with service entrance cable to provide a liquid tight connection to meters and enclosures
N/A

PRODUCT FEATURES

Rugged metallic construction will last the life of the installation

UL LISTED

Standard 514B, UL Listed E195972

GENERAL PRODUCT INFORMATION

Trade Size: 1-1/4 in.
Grommet Opening: .57 in. x .85 in.
UF Wire Size: 3#2

DRAWING DIMENSIONS

Dimension A: 2 in.
Dimension B: 1-27/32 in.
Dimension C: 1-23/64 in.
Dimension D: 1-49/64 in.
Dimension E: 39/64 in.
Dimension F: 1-1/4 in. - 11-1/2

PACKAGING

Package Type: Carton
Ship Carton Qty.: 10
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 50.00
Ship Carton Length (in.): 7.45
Ship Carton Width (in.): 5.37
Ship Carton Height (in.): 5.45
Ctn Weight (Lbs.): 5.00
UPC Number: 050169024751
I2of5: 30050169024752