

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#) [Home Page](#)

[Search](#)

3522 -- Straight Liquidtight Connector 3" Trade Size Insulated



Product Specifications

| | |
|--------------------------------|--|
| Family | Liquidtight Conduit and Cord Connectors |
| Fittings Classification | Steel / Malleable Iron - Straight Connectors |
| Sub Class | Insulated |
| Trade Size | 3" |
| Standard Packaging | Carton |
| Ship Carton Length | 5.0625 |
| Ship Carton Width | 4.75 |
| Ship Carton Height | 5.1875 |
| WT. PER HU. | 361.63 |
| Dimension A | 4-3/4" |
| Dimension B | 1-3/64" |
| Thread Spec. B | 3-8 NPT |
| Dimension C | 3-13/16" |
| Unit Carton Quantity | 1 |
| Ship Carton Quantity | 1 |
| UPC Number | 050169035221 |

Applications

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding

- installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
 - Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
 - Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
 - All metallic components are zinc electro plated for added corrosion protection
 - Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

Compliances

UL CSA

