

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#) [Home Page](#)

3704-3 -- Cord Grip Connector 1" Trade Size .850 - 1.000



Product Specifications

| | |
|--------------------------------|---|
| Family | Liquidtight Conduit and Cord Connectors |
| Fittings Classification | Steel / Malleable Iron Strain Relief Connectors |
| Sub Class | 1 inch Hubs Form 4 |
| Trade Size | 1" |
| Cable Range | .850 - 1.000 |
| Standard Packaging | Carton |
| Ship Carton Length | 6.5 |
| Ship Carton Width | 6.5 |
| Ship Carton Height | 5.125 |
| WT. PER HU. | 34.1 |
| Dimension A | 1-23/32" |
| Thread Spec. A | 1-11-1/2 NPT |
| Dimension B | 21/32" |
| Dimension C | 1-11/16" |
| Unit Carton Quantity | 25 |
| Ship Carton Quantity | 25 |
| UPC Number | 050169370438 |

Applications

- For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
- RACO® liquidtight strain relief cord connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design -- grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification -- eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electro plated for corrosion protection
- Bodies - 3/8" to 1-1/2" Malleable Iron; Nuts - 3/8" to 1" Steel, 1-1/4" Malleable Iron

Compliances

C/UL/US

