

Products


- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

Product Datasheet

[Catalog Home](#) [Home Page](#)

[Search](#)

4752 -- 1/2" Non Metallic Liquidtight 90 Degree Connector - Black - Swivel Lok®



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Nonmetallic Connectors
Sub Class	Nylon for extra Flexible Tubing
Trade Size	1/2"
Standard Packaging	Carton
Ship Carton Length	10.00
Ship Carton Width	5.25
Ship Carton Height	4.3125
WT. PER HU.	21
Dimension F	3.27"
Dimension G	.57"
Dimension H A/C	1.41"
Dimension H A/F	1.30"
Dimension I	1.30"
Dimension J	1.43"
Dimension K	2.00"
Unit Carton Quantity	25
Ship Carton Quantity	25
UPC Number	050169047521

Applications

- For use in dry or wet locations when the conduit and fittings are not subject to physical damage
- Use extra flexible tubing and connectors whenever added flexibility is required for installation, operation, or maintenance

Product Features

- Swivel Lok®, multi-position connector (trade sizes 3/8" to 1") twists from 0° to 90°, easing installation in difficult locations and eliminating need to stock other angle connectors

Compliances

UL Standard 514B CSA - C22.2 #18 NEMA Type 4x, 12 and 13

