



MASONRY BOXES & SUPPORTS

**Block-Loc Masonry Boxes, 3-1/2" Deep - Gangable with Conduit KO's
1 Gang, Gangable**

A59



Catalog #: 689B

APPLICATIONS

For power and data outlets in masonry block walls
Secures masonry box in block wall and prevents box from moving during construction

PRODUCT FEATURES

Integral brackets securely hold box to concrete block from front and back in masonry block walls, even in irregular openings
Quick and accurate positioning
Break off front tabs

UL LISTED

File E195978

CULUS

N/A

COMPLIANCES

They are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System: Conduit
Color: Gray
Country of Origin: USA

CONFIGURATION

End Knockouts: (2) 1/2" - 3/4" TKO
Drawn or Welded: Welded
Raised Ground: No
Gangs: 1
Side Knockout(s): (4) 1/2" - 3/4" TKO
Bottom Knockouts(s): (2) 1/2" - 3/4" TKO

PRODUCT MEASUREMENTS

Depth: 3-1/2 in.
Cubic Inches (cm3): 22.5
Wt. Ea. (Lbs.): 0.968
Product Length (in.): 3.500
Product Width (in.): 3.547
Product Height (in.): 3.906

PACKAGING

Package Type: Boxed
Minimum Pack Qty.: 18
Std. Pkg.: 18
Ship Carton Qty.: 18
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 96.805
Ship Carton Length (in.): 11.125
Ship Carton Width (in.): 10.000
Ship Carton Height (in.): 8.500
Ctn Weight (Lbs.): 17.425
Pallet Qty: 1440
UPC Number: 005169500613
I2of5: 50050169500618