



MASONRY BOXES & SUPPORTS

**Block-Loc 4" Square Tile Cover
1 Gang, 2" Deep**

A59



Catalog #: 786B

APPLICATIONS

For power and data outlets in masonry block walls
Secures masonry box in block wall and prevents box from moving during construction

PRODUCT FEATURES

Integral brackets securely hold box to concrete block from front and back in masonry block walls, even in irregular openings
Quick and accurate positioning
Break off front tabs

UL LISTED

File E195978

CULUS

N/A

COMPLIANCES

They are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System: Conduit
Color: Gray
Country of Origin: USA

CONFIGURATION

Drawn or Welded: Welded
Raised Ground: No
Gangs: 1

PRODUCT MEASUREMENTS

Depth: 2 in.
Cubic Inches (cm3): 14.5
Wt. Ea. (Lbs.): 0.701
Product Length (in.): 2.015
Product Width (in.): 4.188
Product Height (in.): 4.218

PACKAGING

Package Type: Boxed
Minimum Pack Qty.: 25
Std. Pkg.: 25
Ship Carton Qty.: 25
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 70.100
Ship Carton Length (in.): 11.000
Ship Carton Width (in.): 10.750
Ship Carton Height (in.): 8.630
Ctn Weight (Lbs.): 17.525
Pallet Qty: 2000
UPC Number: 050169500668
I2of5: 50050169500663