

ELECTRICAL PRODUCT CATALOG

Wire Pulling Tools Firestopping Pipe Joining Other Products





RECTORSEAL® LOW-VOC SOLVENT CEMENTS

PVC Electrical Conduit 633L O Clear/Gray - medium body solvent cement

Code Description Qty. 55980 1/2 pt. - clear 24 55983 1 pt. - clear 12 55985 1 qt. - clear 12 55986 1 gal. - clear 4 55995 1 pt. - gray 12 55996 1 qt. - gray 12 FEATURES (NSF.

Conduit types I & II

• LEED compliant

- 2 year shelf life
- Meets ASTM D2564 specs

Clear Only

295



Application • Premium polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • Pipe up to 6" schedule 40; 1-1/4" schedule 80 • Remains stable from 0ºF to 120ºF

CTORSEAL

OLVENT CEMENT

525

011

RECTORSEAL

Low-VOC

COLO

Arctic[™] 616L

Clear - medium body PVC solvent cement

Recommended for

 Potable water • Pressure pipe Gas
Conduit
Sewers DWV systems

Also available in gal. can

Code	Description	Qty.
55909	½ pt.	24
55919	1 pt.	12
55948	1 qt.	12
55953	1 gal.	4

FEATURES

· Formulated for use in cold weather

 \bigcirc

 \bigcirc

- LEED compliant
 - · NSF approved for potable water
 - 2 year shelf life
 - Exceeds ASTM D2564 specs

Gene[™]404L

NSF

(NSF.

 \bigtriangledown

Clear - regular body PVC solvent cement

Code	Description	Qty.
55901	¼ pt.	24
55902	½ pt.	24
55904	1 pt.	12
55906	1 qt.	12
55908	1 gal.	4

FEATURES

- · Fast setting formula • LEED compliant
- · NSF approved for potable water • 2 year shelf life
- Exceeds ASTM D2564 & D3138 specs

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints • Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV) **Recommended for** Potable water • Pressure pipe • Gas Conduit Sewers

Pipe Joining

(713-263-7577 800-441-0051

DWV systems