

Rittal – The System.

Faster – better – everywhere.

Laminated Copper Bars – SV 3570.005

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Laminated Copper Bars – SV 3570.005

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Cu lamina: High-purity electrolyte copper Insulation: High-strength vinyl compound, expansion 370%, dielectric strength: 20 kV/mm Fire protection corresponding to UL 94-V0
------------------	---

Note:	May be cut to length as required
--------------	----------------------------------

Product features

Dimensions:	Length: 2000 mm
--------------------	-----------------

Laminated flat copper version:	Number of lamina: 5 Lamina thickness: 1 mm (0.04 ") Lamina width: 20 mm (0.79 ")
---------------------------------------	--

Rated current for temperature increase by:	70 K: 525 A 50 K: 435 A 30 K: 330 A
---	---

Packaging unit:	1 pc(s).
------------------------	----------

Weight/packaging unit:	2.3 kg (5.1 lb.)
-------------------------------	------------------

EAN:	4028177666764
-------------	---------------

Customs tariff number:	74071000
-------------------------------	----------

ETIM 6.0:	EC001522
------------------	----------

ETIM 5.0:	EC001522
eCl@ss 8.0/8.1:	27370303
eCl@ss 7.0/7.1:	27370303
eCl@ss 6.0/6.1:	27370303
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Laminated copper bar, WH: 20x5 mm, L: 2000 mm
Approvals	
Approvals:	C-UR UR UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity