

# Rittal – The System.

Faster – better – everywhere.

## Laminated Copper Bars – SV 3576.005

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Laminated Copper Bars – SV 3576.005

created: 29.05.2018 build on www.rittal.com/us-en



## Product description

**Material:** Cu lamina: High-purity electrolyte copper  
Insulation: High-strength vinyl compound, expansion 370%, dielectric strength: 20 kV/mm  
Fire protection corresponding to UL 94-V0

**Note:** May be cut to length as required

## Product features

**Dimensions:** Length: 2000 mm

**Laminated flat copper version:** Number of lamina: 10  
Lamina thickness: 1 mm (0.04 ")  
Lamina width: 40 mm (1.6 ")

**Rated current for temperature increase by:** 70 K: 1370 A  
50 K: 1145 A  
30 K: 865 A

**Packaging unit:** 1 pc(s).

**Weight/packaging unit:** 7.67 kg (16.9 lb.)

**EAN:** 4028177666825

**Customs tariff number:** 74071000

**ETIM 6.0:** EC001522

<b>ETIM 5.0:</b>	EC001522
<b>eCl@ss 8.0/8.1:</b>	27370303
<b>eCl@ss 7.0/7.1:</b>	27370303
<b>eCl@ss 6.0/6.1:</b>	27370303
<b>eCl@ss 5.1/5.1.4:</b>	27370302
<b>Product description (long):</b>	SV Laminated copper bar, WH: 40x10 mm, L: 2000 mm
<b>Approvals</b>	
<b>Approvals:</b>	C-UR UR UR + C-UR
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity