Rittal - The System.

Faster – better – everywhere.

Wallmountedenclosure Stainlesssteel – WM 8018.515

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Wallmounted enclosure Stainless steel - WM 8018.515 -WM483616N4

created: 24.05.2018 build on www.rittal.com/us-en



Prod	uct	des	crin	tion
riuu	uci	ues	CHID	เมษา

Material: Door: Stainless steel, all-round foamed-in PU seal

Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

Protection category IP 66 IP to IEC 60 529:

Protection category NEMA:

NEMA 4X

Supply includes:

Housing with door(s) Left hand hinge Mounting plate

Wall mounting blind-nuts

Product features

Dimensions: Height: 1200 mm (47 ")

Width: 900 mm (35 ") Depth: 400 mm (16 ")

Material thickness:: Housing: 2 mm (0.08 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Height: 1155 mm (45 ") Mounting plate:

Width: 840 mm (33 ")

© Rittal 2018

1

Lock version:	3-point locking system
Packaging unit:	1 pc(s).
Weight/packaging unit:	93 kg (205 lb.)
EAN:	83537
Approvals	
Approvals:	UL + C-UL

© Rittal 2018