

# Rittal – The System.

Faster – better – everywhere.

## TS 8 Flange Mount Disconnect Floormount Enclosure – TS 8018.814

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS 8 Flange Mount Disconnect Floormount Enclosure – TS 8018.814 - TSFM716320XC

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

Description:	Rittal's Floormount TS 8 combines the strength of unibody floormount enclosures with the flexibility of Rittal's revolutionary modular design. With its double door configuration and wide range of accessories, Rittal's Floormount TS 8 is sure to meet your UL Type 12 needs. Includes operator handle interlocking kit to securely lock most commercially available operator handles to enclosure and door latch.
Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	UL Type 12
Supply includes:	Enclosure frame with door(s) Roof plate Rear panel, detachable 4 eyebolts

## Product features

Dimensions:	Height: 1800 mm (71 ") Width: 1600 mm (63 ") Depth: 500 mm (20 ")
-------------	---

<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	227 kg (500.4 lb.)
<b>EAN:</b>	85557
<b>Approvals</b>	
<b>Approvals:</b>	UL + C-UL