

Rittal – The System.

Faster – better – everywhere.

Cable duct for vertical TS section – TS 8800.570

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Cable duct for vertical TS section – TS 8800.570

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	Width 50 mm, for assembly on a vertical enclosure section in the side panel area.
Benefits:	<p>The cable duct fastening points are co-ordinated with the TS system hole pattern. This eliminates time-consuming drilling work that would be necessary with DIN ducts.</p> <p>The nominal break points of the bars are also designed in combination with the cable ducts for mounting plates.</p> <p>A further nominal break at the mounting plate height allows direct entry to the cable duct.</p>
Material:	Hard PVC Flame-resistant, self-extinguishing
Color:	Similar to RAL 7030
Supply includes:	Cable duct with cover
Note:	Can be shortened for other enclosure sizes.

Product features

Suitable for:	Enclosure type: TS Enclosure type: SE Enclosure type: PC Enclosure type: IW Height: 1800 mm (71 ")
Dimensions:	Height: 1600 mm (63 ") Width: 50 mm (2 ") Depth: 80 mm (3.1 ")
Bar width:	5.5 mm (0.22 ")

Slot width:	4.5 mm (0.18 ")
Packaging unit:	8 pc(s).
Weight/packaging unit:	9.44 kg (20.8 lb.)
EAN:	4028177238015
Customs tariff number:	39269097
ETIM 6.0:	EC000012
ETIM 5.0:	EC000012
eCl@ss 8.0/8.1:	27400703
eCl@ss 7.0/7.1:	27400703
eCl@ss 6.0/6.1:	27400703
eCl@ss 5.1/5.1.4:	27189224
Product description (long):	TS Cable duct for vertical TS section, WHD: 50x1600x80 mm
Approvals	
Certificates:	EAC