

# Rittal – The System.

Faster – better – everywhere.

## ► OM support without contact system – SV 9340.270

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# OM support without contact system – SV 9340.270

created: 24.05.2018 build on www.rittal.com/us-en



## Product description

**Description:** For mounting of switchgear with external power supply.

**Material:** Polyamide (PA 6.6)  
Fire protection corresponding to UL 94-V0

**Color:** Chassis: RAL 7035

## Product features

**Suitable for busbars:** with cross-section height: 5 mm  
with cross-section height: 10 mm

**Number of poles:** 3-pole

**For bar systems with center-to-center spacing:** 60 mm

**Dimensions:** Height: 272 mm (11 ")  
Width: 55 mm (2.2 ")

**Support Frame:** Height: 237 mm (9.3 ")  
Width: 55 mm (2.2 ")

**Number of support rails:** 1

**Height of support rails:** 10 mm (0.39 ")

**Support rail type:** TS 55D-V

<b>Support frame support:</b>	yes
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	0.26 kg (0.6 lb.)
<b>EAN:</b>	4028177502475
<b>Customs tariff number:</b>	39269097
<b>ETIM 6.0:</b>	EC001166
<b>ETIM 5.0:</b>	EC001166
<b>eCl@ss 8.0/8.1:</b>	27400607
<b>eCl@ss 7.0/7.1:</b>	27400607
<b>eCl@ss 6.0/6.1:</b>	27400607
<b>eCl@ss 5.1/5.1.4:</b>	27370302
<b>Product description (long):</b>	SV OM Support, WH: 55x272 mm, support frame, support rail TS 55D-V, without contact system
<b>Approvals</b>	
<b>Approvals:</b>	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity