

# Rittal – The System.

Faster – better – everywhere.

## Connection Adapters – SV 9342.210

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Connection Adapters – SV 9342.210

created: 24.05.2018 build on www.rittal.com/us-en



## Product description

<b>Material:</b>	Cover: ABS Chassis: Polyamide (PA 6.6) Chassis 3439.010: Fiberglass-reinforced, thermoplastic polyester (PBT) Fire protection corresponding to UL 94-V0 Chassis: Polyamide (PA 6.6)
<b>Color:</b>	RAL 7035
<b>Note:</b>	The technical data may vary for UL applications. UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050.

## Product features

<b>Suitable for busbars:</b>	with cross-section height: 5 mm (0.2 ") with cross-section height: 10 mm (0.39 ")
<b>Number of poles:</b>	3-pole
<b>For bar systems with center-to-center spacing:</b>	60 mm
<b>Dimensions:</b>	Height: 215 mm (8.5 ") Width: 20 mm (0.79 ")
<b>Rated operating voltage:</b>	690 V, 3~
<b>Connection for round conductor cross-</b>	Fine wire with wire end ferrule: 2,5 mm <sup>2</sup> - 10 mm <sup>2</sup> Multi-wire: 2,5 mm <sup>2</sup> - 10 mm <sup>2</sup>

<b>sections:</b>	Solid: 2,5 mm <sup>2</sup> - 10 mm <sup>2</sup>
<b>Rated current (max.):</b>	63 A
<b>Cable outlet:</b>	Bottom
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	0.22 kg (0.5 lb.)
<b>EAN:</b>	4028177503601
<b>Customs tariff number:</b>	85369010
<b>ETIM 6.0:</b>	EC001531
<b>ETIM 5.0:</b>	EC001531
<b>eCl@ss 8.0/8.1:</b>	27370304
<b>eCl@ss 7.0/7.1:</b>	27370304
<b>eCl@ss 6.0/6.1:</b>	27370304
<b>eCl@ss 5.1/5.1.4:</b>	27370302
<b>Product description (long):</b>	SV Connection adaptor, 63 A, 690 V, 3-pole, cable outlet bottom, round conductor connection 2,5-10 mm <sup>2</sup>
<b>Approvals</b>	
<b>Approvals:</b>	ABS C-UL DNV-GL UL + C-UL
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity