

Product data sheet

Characteristics

25S40FSS

TRANSFORMER DRY 1PH 25KVA

480V-120/240V

Product availability : Stock - Normally stocked in distribution facility



Price* : 9606.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary voltage	480 V
Secondary voltage	120/240 V
Number of tap-offs	2 5 % FCBN

Complementary

Box number	15B
Phase	1 phase
Primary voltage	480 V : 120/240 V
Rated power in VA	25 kVA
Temperature rise	115 °C
Height	20 in
Width	15 in
Depth	13.5 in
Enclosure mounting	Wall mounted
Enclosure material	Stainless steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CULus UL listed CSA

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
----------	-------------------------

Discount Schedule	PE2
GTIN	00785901836896
Nbr. of units in pkg.	1
Package weight(Lbs)	402
Returnability	N
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------