

Product availability : Stock - Normally stocked in distribution facility



Price* : 181.70 USD



Main

Device application	Manual reversing control
Enclosure type	Indoor enclosure standard environment
Range of product	A

Complementary

Control type	Standard
Depth	4.61 in
Device mounting	Flush
Electrical connection	Screw clamp terminal
Height	5.38 in
Motor power hp	1.5 hp , 115 V AC , 1 phase 2 hp , 230 V AC , 1 phase 2 hp , 200/575 V AC , 3 phases
Motor starter type	Reversing
Permissible voltage	<= 600 V AC <= 250 V DC
Switch actuation	Forward (maintained) Reverse (momentary)
Width	3.26 in

Environment

NEMA degree of protection	NEMA 1
Product certifications	UL listed file E42243 CCN NLRV CSA LR 25490 class 3211 05

Ordering and shipping details

Category	21116 - 2601
Discount Schedule	CP1

GTIN	00785901015055
Nbr. of units in pkg.	1
Package weight(Lbs)	1.3100000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------