

Product data sheet

Characteristics

3T5F

TRANSFORMER DRY 3PH 3KVA 480V-240V

Product availability : Stock - Normally stocked in distribution facility



Price* : 2016.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary voltage	480 V delta
Secondary voltage	240 V delta
Number of tap-offs	2 5 % FCBN

Complementary

Box number	12C
Phase	3 phases
Primary voltage	480 V delta : 240 V delta
Rated power in VA	3 kVA
Temperature rise	115 °C
Height	13.5 in
Width	14.75 in
Depth	9 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	UL listed cULus CSA

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2

GTIN	00785901855989
Nbr. of units in pkg.	1
Package weight(Lbs)	140
Returnability	N
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------