Product data sheet
Characteristics

750SV1F
XFMR DRY 1PH .75KVA 240X480V-120/240V

Product availability : Stock - Normally stocked in distribution facility

Price* : 460.00 USD

Main

Product or component type	Dry Sealed Transformer
Primary voltage	240 x 480 V
Secondary voltage	120/240 V
Number of tap-offs	0

Complementary

Box number	6A
Phase	1 phase
Primary voltage	240 x 480 V : 120/240 V
Rated power in VA	0.75 kVA
Temperature rise	115 °C
Height	6.69 in
Width	6.19 in
Depth	4.69 in
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CSA UL listed cULus

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	00785901876250
Nbr. of units in pkg.	1
Package weight(Lbs)	17.449999999999999
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months