

Product availability : Stock - Normally stocked in distribution facility



Price* : 1808.00 USD



Main

Product or component type	Starter
Range of product	S
Line Rated Current	45 A
Product certifications	CSA NEMA UL listed
Control circuit	Common control circuit
Control type	2 momentary push-buttons (START-STOP)
NEMA degree of protection	NEMA 12 painted sheet steel
Rated power in HP	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	2
[Uc] control circuit voltage	208 V AC 60 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901471707
Nbr. of units in pkg.	1
Package weight(Lbs)	17.43

Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant

Contractual warranty

Warranty period	18 months
-----------------	-----------
