

Product availability : Stock - Normally stocked in distribution facility



Price\* : 207.00 USD



### Main

|                    |                                 |
|--------------------|---------------------------------|
| Device short name  | C                               |
| Enclosure type     | Standard                        |
| Head type          | Turret head rotary lever type C |
| Provided equipment | Receptacle                      |
| Series name        | Heavy duty                      |

### Complementary

|                               |  |
|-------------------------------|--|
| Line Rated Current            | 10 A   |
| Body material                 | Zinc alloy                                       |
| Cable entry                   | NPT conduit entry 0.5 in                         |
| Contact code designation      | R300<br>A600                                     |
| Contact form                  | Form ZZ DPDT-DB                                  |
| Contacts material             | Silver alloy (Ag/Ni)                             |
| Contact operation             | Snap action                                      |
| Contacts type and composition | 2 NO/2 NC  |
| Maximum displacement angle    | 90 °   |
| Permissible voltage           | <= 600 V   |
| Pilot light                   | Without pilot lamp                               |
| Specificity of operator       | Standard pre-travel                              |
| Switch actuation              | CCW  |
| Tilting angle                 | 10 °   |
| Torque value                  | 4 lbf.in   |
| Tripping angle                | 4 °  |
| Type of operator              | Spring return lever arm to be ordered separately |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Environment

|                                       |                        |
|---------------------------------------|------------------------|
| Ambient air temperature for operation | -20...185 °F           |
| Product certifications                | CE<br>CSA<br>UL listed |

## Ordering and shipping details

|                       |                               |
|-----------------------|-------------------------------|
| Category              | 21499 - 9007 C LIMIT SWITCHES |
| Discount Schedule     | DS1                           |
| GTIN                  | 00785901538288                |
| Nbr. of units in pkg. | 1                             |
| Package weight(Lbs)   | 1.25                          |
| Returnability         | N                             |
| Country of origin     | MX                            |

## Offer Sustainability

|                                  |  |
|----------------------------------|--|
| Sustainable offer status         | Not Green Premium product  |
| RoHS (date code: YYWW)           | Will not be compliant<br>Will not be compliant   |
| REACH                            | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold |
| Product environmental profile    | Available  |
| Product end of life instructions | Need no specific recycling operations  |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|