9050AO11EV02



Main

Range of product	9050A/H
Product or component type	Timer
Time delay type	On-delay
Time delay range	0.1 s1 min
Switch function	SPDT
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Contact operation	Time delayed 1 NO + 1 NC Instantaneous 1 NO + 1 NC
Line Rated Current	15 A

Complementary

Maximum switching voltage	600 V AC
Electrical connection	Screw-clamp terminals
Reset response time	29 ms - on-delay 27 ms - off-delay
Mounting support	Panel

Environment

ambient air temperature for operation	68104 °F	
product certifications	CSA UL listed	Tained be
height	2.64 in (67 mm)	- GO S
width	4.02 in (102 mm)	
depth	4.37 in (111 mm)	

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1444 - Schneider Electric declaration of conformity	Compliant - since 1444 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months