

Product availability : Stock - Normally stocked in distribution facility



Price* : 2229.00 USD



Main

Product or component type	Industrial Control Transformer
Rated power in VA	3000 VA
Primary voltage	220 x 440 V 240 x 480 V 230 x 460 V
Secondary voltage	120/240 V 110/220 V 115/230 V
Range of product	T

Complementary

Phase	1 phase
Rated power in VA	3000 VA per UL 3000 VA per CSA 3000 VA per NOM 2000 VA per CE
Primary voltage	220 x 440 V : 110/220 V 230 x 460 V : 115/230 V 240 x 480 V : 120/240 V
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	8.75 in
Width	9 in
Depth	7.24 in
Material	Copper winding
Product compatibility	FSC2

Environment

Product certifications	UL listed file E61239 CE
------------------------	-----------------------------

NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16205 - 9070 T (NOT TF) 3000 - 5000VA
Discount Schedule	CP8
GTIN	00785901326311
Nbr. of units in pkg.	1
Package weight(Lbs)	59.550000000000004
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	10 years
-----------------	----------