

Product availability : Stock - Normally stocked in distribution facility



Price* : 230.00 USD



Main

Enclosure type	Open box
Range of product	TF

Complementary

Depth	3.34 in
Device composition	Top fuse disconnecter
Electrical connection	Screw clamp terminal
Fuse type	0.41 x 1.50 in CC fuse mounting on top
Height	4.25 in
Material	Copper winding
Mounting support	Panel
Network number of phases	1 phase
Primary voltage	550 V 575 V 600 V
Rated power in VA	100 VA
Secondary voltage	110 V 115 V 120 V
Temperature rise	55 °C
Width	3.38 in

Environment

Insulation temperature	221 °F (105 °C)
Product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
Standards	NEC 450 UL 508

Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901736790
Nbr. of units in pkg.	1
Package weight(Lbs)	4.5
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------